

Declaration of Conformity

In accordance with UK Government Guidance

Product Model: Multi-layer parquet flooring (3-layer wooden parquet)

Specifications: Total thickness: **14.2mm/ 22mm**

Width: **145/190/240/290mm**

Length: **1820/2130/2450mm**

Surface treatment: **UV Urethane/Lacquer, UV-Oil**

This wood flooring is intended for indoor installations in dry areas. Suitable for floating, glue or nail down installations in accordance with the manufactures instructions and harmonized standard EN14342:2013

The data of conformity is accordance to CE certificate no ZSTV-021-020

The performance of the product corresponds as declared. The manufacturer is solely responsible for the preparation of this statement in accordance with regulation (EU) No.305/2011

1. Testing Laboratory No. 1030.1 accredited by CAI according to ČSN EN ISO/IEC 17025:2005
2. Testing Laboratory No. 1001 accredited by Czech institute for accreditation according to EN ISO/IEC 17025:2018
3. Testing Laboratory accredited by SNAS Reg, No 104/2-331

-Certificate number ZSTV-021-19

-Report Number R-001-19, 15 November 2019, Notified Body No.1389

-Report Number 1389-CPR-028-19 rev. 1, 28 April 2020, Notified Body No.1389

-Test report AZL-STV-026-19, 14 November 2019, Testing Laboratory No 1030.1

-Test report AZL-N-006-19, 29 August 2019, Testing Laboratory No 1030.1

-Test Report 810/20/027/19, 24 September 2019, Lignotesting a.s., Technická 5, 821 04 Bratislava, Notified Body No.1478 ¹

This declaration is issued under the sole responsibility of the product manufacturer.

Essential characteristics	Performance		Harmonised technical specification
Mass density	≥ 650 kg/m ³		
Emission of formaldehyde	EN 14342:2013 ~ E1		EN14342:2013, Annex A Table B.1 Class E1 ≤ 0.124 mg/ m ³
	JAS F****/SE0		Actual test result refers ¹
Content of pentachlorophenol	≤ 0.1 ppm		EN14342:2013, Article 4.3.2 <5 ppm
Breaking strength	NPD		EN14342:2013, Article 4.5
Slip resistance	PTV 45 (UV Lacquer Bona)		EN14342:2013, Article 4.6
	PTV 42 (UV Lacquer Klumpp)		
	PTV 44 (UV Oil Klumpp)		
Biological durability	Class 1		EN 14342, Article 4.8 EN 335-2
Reaction to Fire	14.2mm	≥ D _{fi} - s1	Euroclass according to EN 13501-1) Reaction to fire classes for flooring C _{fi} , D _{fi} , E _{fi} , F _{fi}
	22 mm	≥ C _{fi} - s1	
Thermal Resistance	14.2mm	0,098 R (m ² .K)/W	EN14342:2013, Article 4.7
	22 mm	0,148 R (m ² .K)/W	
Thermal Conductivity	14.2mm	0,14 λ W/(m.K)	EN14342:2013, Article 4.7
	22 mm	0,15 λ W/(m.K)	

Signed for and on behalf of the manufacturer by:



FORESTRY
TIMBER HOLDINGS LIMITED
REG NUMBER: 019804V

Gurjeet Singh.

CEO 1 September 2022