PECAN

After Oak Collection

FORESTRY
TIMBER HOLDINGS LIMITED

INDOOR AIR QUALITY		PERFORMANCE
	EN 16516:2017 ISO 16000 3, 6, 9, 11 ASTM D5116-10	
	Émissions dans l'air intérieur A+ Label (France) Volatile Organic Compound (VOC)	A+
LEED® v4.1	Building Design & Construction	Meets requirements on some products
AgBB Evaluation	Committee for Health-Related Evaluation of Building products (Germany)	Meets requirements on some products
BREEAM® International	BREEAM® International New Construction v2 (2016)	Exemplary Level on some products
BREEAM® NOR	BREEAM® NOR New Construction v1.2 (2019)	Meets requirements on some products
	No Added Formaldehyde Guidelines, V3-0 (APRIL 2013)	No added compounds using urea formaldehyde or phenol formaldehyde in conformance to the SCS. Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Less than/equal to 0.5 mg/m³
	Indoor Air Quality (US Standard)	Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³
NO FORMALDEHYDE	EN 14342:2013 EN 717-1	F☆☆☆☆~ SE0 ≤ 0,034 mg/m³

SUSTAINABILITY		CERTIFICATION BODY	PERFORMANCE
	PEFC Certified and PEFC Controlled sources sawn timber and engineered flooring SCS-PEFC/COC-008866	SCS Global Services, USA	Available on request

PECAN

After Oak Collection

FORESTRY
TIMBER HOLDINGS LIMITED

TESTED & CERTIFIED	PERFORMANCE
CE (Conformité Européenne) European Standard EN 14342:2013	Compliant
Declaration of Conformity United Kingdom in accordance with CE certificate no ZSTV-021-020 European Standard EN14342:2013	Compliant
Sucofindo International Certification Services VLK 00041	Compliant

HARDWOOD ENGINEERED FLOORING

Species	Pecan
Surface Texture	Smooth
Finish	UV Urethane Bona UV Oil UV Urethane HP
Grade	Rustic
Construction	Three-layered Engineered planks with Hevea Core

DIMENSION

Thickness	14.2mm	or	22mm
	9/16”	or	7/8”
Plank Widths	190mm		
	7 ½”		
Plank Length	2130mm		
	7’		
Herringbone	120mm	X	840mm
	4 ¾”	X	2’ 9”

DIMENSION

Chevron Single Plank	120mm	X	770mm
	4 ¾"	X	2' 6"

INSTALLATION

Engineered Planks	Tongue & Groove - Välinge 5G Installation Tongue & Groove Floating, Glue or Nail down

USAGE

Recommended Installation	Suitable for use in residential projects. For commerical projects we recommend additional treatments

SLIP RATING

EN 14342:2013 CEN/TS 15676	PTV 45 (UV Bona) PTV 44 (UV Oil) UV HP - ASTM D4060/DIN EN438 ***PTV = Mean pendulum swing value***

FIRE RATING

EN 14342:2013 EN 13501-1	14.2mm Class D_{fl} - s1 22mm Class C_{fl} -s1

FORESTRY
TIMBER HOLDINGS LIMITED