

INDOOR AIR QUALITY PERFORMANCE

	EN 16516:2017 ISO 16000 3, 6, 9, 11 ASTM D5116-10	
	Émissions dans l'air intérieur A+ Label (France) Volatile Organic Compound (VOC)	A+
LEED® v4.1	Building Design & Construction	Meets requirements on some products
AgBB Evaluation	Committee for Health-Related Evaluation of Building products (Germany)	Meets requirements on some products
BREEAM® International	BREEAM® International New Construction v2 (2016)	Exemplary Level on some products
BREEAM® NOR	BREEAM® NOR New Construction v1.2 (2019)	Meets requirements on some products
	No Added Formaldehyde Guidelines, V3-0 (APRIL 2013)	No added compounds using urea formaldehyde or phenol formaldehyde in conformance to the SCS. Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Less than/equal to 0.5 mg/m <sup>3</sup>
	Indoor Air Quality (US Standard)	Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m <sup>3</sup>
NO FORMALDEHYDE	EN 14342:2013 EN 717-1	F☆☆☆☆~ SE0 ≤ 0,034 mg/m <sup>3</sup>

SUSTAINABILITY CERTIFICATION BODY PERFORMANCE

	FSC 100%; FSC Mix; FSC Controlled Wood SCS-COC-008866	SCS Global Services, USA	Available on request
	PEFC Certified and PEFC Controlled sources sawn timber and engineered flooring SCS-PEFC/COC-008866	SCS Global Services, USA	Available on request

# OAK

Variante Collections

## TESTED & CERTIFIED PERFORMANCE



CE (Conformité Européenne)  
European Standard EN 14342:2013

Compliant



Declaration of Conformity  
United Kingdom in accordance with  
CE certificate no ZSTV-021-020  
European Standard EN14342:2013

Compliant



Sucofindo International Certification  
Services VLK 00041

Compliant

## HARDWOOD ENGINEERED FLOORING



Species

Western European Oak



Surface Texture

Smooth or brushed



Finish

UV Urethane Bona  
UV Oil  
UV Urethane HP



Grade

Variante



Construction

Three-layered Engineered planks with Hevea Core

## DIMENSION



Thickness

14.2mm or 22mm  
9/16" or 7/8"



Plank Widths

145mm 190mm 240mm  
5 3/4" 7 1/2" 9 1/2"



Plank Length

2130mm 2450mm  
7' 8'

## INSTALLATION



Engineered Planks

Tongue & Groove - Vålinge 5G Installation  
Tongue & Groove  
Floating, Glue or Nail down

## USAGE



Recommended Installation

Suitable for use in residential projects. For commercial projects we recommend additional treatments

## SLIP RATING



EN 14342:2013  
CEN/TS 15676

PTV 45 (UV Bona)  
PTV 44 (UV Oil)  
UV HP - ASTM D4060/DIN EN438  
**PTV = Mean pendulum swing value**

## FIRE RATING



EN 14342:2013  
EN 13501-1

14.2mm Class  $D_{fl}$  - s1  
22mm Class  $C_{fl}$  -s1