




PECAN


After Oak Collection



INDOOR AIR QUALITY PERFORMANCE

	EN 16516:2017 ISO 16000 3, 6, 9, 11 ASTM D5116-10	
	Émissions dans l'air intérieur A+ Label (France) Volatile Organic Compound (VOC)	A+
LEED® v4.1	Building Design & Construction	Meets requirements on some products
AgBB Evaluation	Committee for Health-Related Evaluation of Building products (Germany)	Meets requirements on some products
BREEAM® International	BREEAM® International New Construction v2 (2016)	Exemplary Level on some products
BREEAM® NOR	BREEAM® NOR New Construction v1.2 (2019)	Meets requirements on some products
	No Added Formaldehyde Guidelines, V3-0 (APRIL 2013)	No added compounds using urea formaldehyde or phenol formaldehyde in conformance to the SCS. Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Less than/equal to 0.5 mg/m ³
	Indoor Air Quality (US Standard)	Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m ³
NO FORMALDEHYDE	EN 14342:2013 EN 717-1	F☆☆☆☆~ SE0 ≤ 0,034 mg/m ³

SUSTAINABILITY CERTIFICATION BODY PERFORMANCE

	PEFC Certified and PEFC Controlled sources sawn timber and engineered flooring SCS-PEFC/COC-008866	SCS Global Services, USA	Available on request
---	---	-----------------------------	----------------------

TESTED & CERTIFIED PERFORMANCE



CE (Conformité Européenne)
European Standard EN 14342:2013

Compliant



Declaration of Conformity
United Kingdom in accordance with
CE certificate no ZSTV-021-020
European Standard EN14342:2013

Compliant



Sucofindo International Certification
Services VLK 00041

Compliant

HARDWOOD ENGINEERED FLOORING



Species

Pecan



Surface Texture

Smooth



Finish

UV Urethane Bona
UV Oil
UV Urethane HP



Grade

Rustic



Construction

Three-layered Engineered planks with Hevea Core

DIMENSION



Thickness

14.2mm or 22mm
9/16" or 7/8"



Plank Widths

190mm
7 1/2"



Plank Length

2130mm
7'



Herringbone

120mm X 840mm
4 3/4" X 2' 9"

DIMENSION



Chevron Single Plank

120mm X 770mm
4 3/4" X 2' 6"

INSTALLATION



Engineered Planks

Tongue & Groove - Välinge 5G Installation
Tongue & Groove
Floating, Glue or Nail down

USAGE



Recommended Installation

Suitable for use in residential projects. For commercial projects we recommend additional treatments

SLIP RATING



EN 14342:2013
CEN/TS 15676

PTV 45 (UV Bona)
PTV 44 (UV Oil)
UV HP - ASTM D4060/DIN EN438
PTV = Mean pendulum swing value

FIRE RATING



EN 14342:2013
EN 13501-1

14.2mm Class D_{fl} - s1
22mm Class C_{fl} -s1